



Features:

- No UV or IR light radiation.
- Provide 115° beam angles.
- Using high luminous efficiency LED, a single white module's luminous flux can be up to 47lm, luminous efficiency 39lm/w
- UV Stabilized plastic Lens and plastic Lamp Shell
- Life expectancy: 3 years \geq 13000 hours (L_{70}).
- All-inclusive aluminum process and PCB board ensure good heat dissipation and longer life
- Correlated Color Temperature: 6500-7000K
- Operating temperature: -20°C ~ +60°C.
- DC12V
- IP Degree: IP65
- Convenient to install: The standard cascade number 50pcs modules. Two modules make a unit, no cut between each two modules.

Benefits

- Energy Cost Savings:
Over 80% Compared to Incandescent.
- Solid-State:
High-Shock & High-Vibration Resistant,
Both Electrical and Mechanical
- Eco-Friendly:
No Mercury, No Lead Content
- No Hazardous Emissions:
No UV or IR Radiation
- Constant Light Output:
Even Lighting, Non-Halation
- No glare, no stroboscopic
- Fine heat output structure

Application:

- Channel letters backlighting
- Indoor lighting and decoration
- Architecture lighting
- Advertising light box backlighting
- Sign board backlighting
- Commercial sign backlighting

Product Specifications:

Lamp Shell	Plastic
Voltage	DC12 V
Wattage	1.2W/pcs
Color	White
IP	IP65
Operating Temperature	-20℃ ∞ +60℃
Storage Temperature	-30℃ ∞ +70℃
Net Weight per piece (g)	500g
Warranty period	36 month
Size	67.4MM×16MM×6MM
Standard connection	50pcs
Conforming standard	CE\ROHS

Tips:

- Tolerable range for luminous flux,color rendering and rated power: $\pm 10\%$.
- Tolerable range for operating voltage: $\pm 5\%$.
- Testing temperature: $25 \pm 1^{\circ}\text{C}$.
- Warranty limited:3 years or 13000 hours;Whichever comes first.
- The maximum cascade number is 50pcs when supply power at one end. Do not exceed.

Product Selection Guide:


Product	Beam Angle	Total Lumens	CCT	Luminous Efficiency	CRI
LS-5630W2R	115°	47 \pm 5%	6500-7000K	39lm/W	PF \geq 70

LS-5630W2R

① ② ③ ④ ⑤

- ① LS: led Modules
- ② 5630: 5630 LED
- ③ W: W (white)
- ④ 2: 2 pcs of led per module
- ⑤ R: DC12V


Product Dimensions:



NOTES:

1. All dimensions unit in mm
2. Tolerances is ± 0.5 mm unless otherwise noted.

Package Dimension



Installation Instructions and Warnings:

- Carton size:520*370*260mm:
- Each string has 50PCS, 2strings in one bag, totally 100 pieces;
- Each inner bag has 6 small bags of modules (600PCS),while each carton has 2 inner bags (1200 PCS);
- Net weight(NW): 13.49 (1±5%)Kg:
- Gross weight (GW): 15.63 (1±5%)Kg: